

2year
warranty

MK Series Audio Video Entry Security System



**Black & White
Video Entry Intercom**

MK Audio Video Entry

System Configuration



Features

- One door to 3 rooms.
- Modern styling.
- Communication between monitors.
- Vandal resistant door stations available.
- Simple wiring.
- Wide angle lens on door station.
- Composite video output available (NTSC). (MKCABLE required)
- MK-S1GD kit available containing MK-DH door station, one MK-1GD monitor and power supply.

Specifications

Power Source	DC 18V.
Consumption	MK-1GD: (Max.) 650mA. MK-1HD: (Max.) 450mA. MK-2SD: (Max.) 150mA.
Power Supply	Use PS-182 for 2 or 3 monitors.
Calling	Chime, audio and image.
Communication	Simultaneous with handsets, handsfree at door.
Door release	AC 12V, 0.4A dry-closure contact.
Wiring	2 conductors to door. 4 conductors between room stations.
Distance	
Diameter	1 mm
Door to MK-1GD	200 m (polyethylene over 100 m)
MK-1GD to farthest sub	75 m
MK-1GD to PS-182	10 m

Additional Options

2-call Door Stations.



MK-2DA
2-call surface mount resin panel.

EL-9S
Door release, AC12V, 0.35A.

IER-2
Call extension speaker.

KAW-D
30° angle box (for MK-DH).

MKW-P
Gang box mounting plate, 60/83.5 mm for MK-DV.

KC-32EU
Picture memory unit.

MKCABLE
Cable for connection to service switch and NTSC output.

Your local Aiphone reseller:

2year
warranty

COMMUNICATION SYSTEMS
AIPHONE[®]
HOME, BUSINESS, INDUSTRY.