



A.D.S MasterMatic PTY LTD

4 Colrado ct
Hallam, VICTORIA 3803
www.adsmastermatic.com.au
info@adsmastermatic.com.au
P: (03) 9796 3611
F: (03) 9796 3823



S-30 SUPER HEAVY DOOR AUTOMATIC DOOR SYSTEM SERIES



S-30 SUPER HEAVY DOOR




**DURABLE HANGING
TWIN WHEEL**




**S-30 CONTROLLER
WITH CTB DEVICE**

**DC24V 250W BRUSHLESS DC
MOTOR (PLANETARY GEAR)**



Our Operator's Features

- ★ Install in factories, airports, military bases and other high security areas to be protected.
- ★ Special tracks and wheels, carrying heavier and more stable.
- ★ Using a large radius of the pulley and greatly reduce noise and enhance the useful time.
- ★ DC24V 250W Brushless DC Motor. (Planetary Gear)



MEASURE : mm

TYPE	S-30	
MODEL	SINGLE-WINGED	BI-PARTING
DOOR WEIGHT	2000kg X1(DOOR)	1500kg X2(DOOR)
DOOR WIDTH	1M~6M	1M~6M
INSTALL WAY	SURFACE INSTALL	SURFACE INSTALL
MOTOR	DC24V 250W BRUSHLESS DC MOTOR (PLANETARY GEAR)	
CONTROL	STANDARD MICRO-CONTROL	
POWER CONSUMPTION	250W	
VOLTAGE	AC100V~240V	
ENVIRONMENTAL TEMPERATURE	-20°C~+50°C	
VOLUME	65 DECIBEL(MAX.)	
STARTING SPEED	150mm/SEC.	120mm/SEC.
STARTING TIMES	0~20 SEC. (REGULABLE)	
TRANSMISSION IMPORTANT CONDITION	ROLLER CHAIN 40-1R	
OPENING DOOR RANGE	FULL/HALF-OPEN (REGULABLE)	
PFC POWER EFFICIENCY	0.95(IN AC100V FULL LOAD)	
TRACTION FORCE	WHEN POWER OFF THE DOOR CAN BE OPENED BY MANUAL	